



### Allen Wrench



DIN 911  
ISO 2936

Order	d	l	l1
AA.15	1.5	45	15
AA.20	2	50	17
AA.25	2.5	57	20
AA.30	3	64	22
AA.35	3.5	68	25
AA.40	4	72	28
AA.45	4.5	78	30
AA.50	5	83	32
AA.60	6	94	37
AA.70	7	99	40
AA.80	8	105	43
AA.90	9	111	46
AA.100	10	119	49
AA.120	12	134	56
AA.140	14	140	56
AA.160	16	165	75
AA.170	17	160	63
AA.190	19	180	70
AA.220	22	200	80
AA.240	24	224	90
AA.270	27	250	100

### Allen Wrench, Long Type



DIN 911  
ISO 2936

Order	d	l	l1
AU.20	2	100	16
AU.25	2.5	112	18
AU.30	3	126	20
AU.35	3.5	135	21
AU.40	4	140	25
AU.45	4.5	150	25
AU.50	5	160	28
AU.60	6	180	32
AU.70	7	190	34
AU.80	8	200	36
AU.90	9	212	38
AU.100	10	224	40
AU.110	11	240	42
AU.120	12	250	45
AU.130	13	266	50
AU.140	14	280	56
AU.170	17	320	63

### Allen Wrench Set



Order	Diameter
AAS10 (10pcs)	2-2.5-3-4 5-6-7-8 9-10
AAS12 (12pcs)	2-2.5-3-4 5-6-7-8-9 10-12

### Die & Mould Mounting Kit

Code: **IW3C14**



Capacity: 16 mm  
Max. Torque: 1492 Nm (150Kg.)  
Length: 190 mm  
Min. Hose Size: 10 mm  
Air Pressure: 6.3 Bar

1/2" Air Nutrunner

1/2" Allen End

Code: **111300610..**




There is 1 pcs. allen end per dimension in the Die & Mould Mounting Kit.

Order	d	l	In Kit
11130061006	6	60 mm	1 pcs.
11130061008	8		1 pcs.
11130061010	10		1 pcs.
11130061012	12		1 pcs.
11130061014	14		1 pcs.




### Round Head Allen Wrench




Order	d	l	l1
BA.20	2	50	16
BA.25	2.5	60	18
BA.30	3	63	20
BA.40	4	70	25
BA.50	5	80	28
BA.60	6	90	32
BA.80	8	100	36
BA.100	10	112	38

### Key Wrench for Torx Head




Order	d	l	l1
TX.T6	T6	42	16
TX.T7	T7	48	16
TX.T8	T8	48	16
TX.T9	T9	48	16
TX.T10	T10	51	17
TX.T15	T15	54	18
TX.T20	T20	57	19
TX.T25	T25	60	20

### Hexagon Key Wrench



Order	d	l	l1
TA.20	2	139	52
TA.25	2.5	153	55
TA.30	3	153	55
TA.35	3.5	179	70
TA.40	4	179	70
TA.45	4.5	200	84
TA.50	5	200	84
TA.60	6	221	103
TA.70	7	236	106
TA.80	8	255	117
TA.100	10	285	132


### Round Head Hex. Key Wrench



Round on the long side

Order	d	l	l1
BT.25	2.5	153	55
BT.30	3	153	55
BT.40	4	179	70
BT.50	5	200	84
BT.60	6	221	103
BT.80	8	255	117

### Hexagon Socket Wrench




Order	d	l	l1
LA.4	4	210	125
LA.6	6	210	125
LA.7	7	220	125
LA.8	8	220	125
LA.10	10	220	125
LA.12	12	230	125
LA.14	14	230	125

### "T" Allen Wrench

Code: **AKH**




Functional use with strong steel thick body and sleeve system on it



### "T" Type Triple Hexagon Head Allen Wrench

Free / quick rotating via cold-rolled hexagon profile and sleeve on it and it is ready to process with robust and free insert handle. Chrome vanadium steel and black ends are suitable for screws in depth under high torques. Thanks to its handle, screwdriver set can be optimally adapted according to the position of the screw.



Order (AKH)	Dia	l	l1
AKH.03	3	125	63
AKH.04	4	180	87
AKH.05	5	180	90
AKH.06	6	210	105
AKH.08	8	250	125
AKH.10	10	300	145
AKH.12	12	320	160
AKH.14	14	340	165

### 360° Rotary Arm



Please visit [www.guvenal.net](http://www.guvenal.net) for product video.