



EDM Polishing Stones

Code: EG..

EDM Polishing Stones are produced to make excellent levelling / polishing on rough surfaces. It takes the shape of the surface it works with by making fast cutting. It works precisely on figured surfaces. EDM Polishing Stones are suitable for manual and Air File Tool use. Hard and complex, especially in deep areas, long polishing stones can be selected. At flat and wide areas, short polishing stones can be less fragile by avoiding skidding.

When using by hand, use a holder. Different type holders at our Air File Tools present extensive usage opportunity.

For softer and clean polishing stone usage, you can use your polishing stone by steeping in low oil liquid etc. To use right graduation from coarse polishing stone to fine one on surface is important. Cleaning of operation area is also important.

EDM Polishing Stone Types

	,	71			
EGK	EGD	EGY	EGU	Grit	Operation
///				# 120	
				# 150	Levelling
				# 180	
width x length (mm)	width x length (mm)	diameter x length (mm)	width x length (mm)	# 220	
, , ,	, , ,	, , ,		# 280	Pre-
4 x 4 x 100	6 x 3 x 150	Ø 6 x 150	8 x 8 x 150	# 320	polishing
6 x 6 x 150	13 x 3 x 150	Ø 8 x 150	10 x 10 x 150	# 400	
8 x 8 x 150	13 x 6 x 150	Ø 10 x 150	_	# 600	
		•		# 800	Finishing
10 x 10 x 150	-	Ø 12 x 150	-	# 1000	

Order: Type. Dimension. Grit

Order Example: EGK. 4 x 4 x 100. 320

EDM Polishing Stone Holders

	Manually Operated			Air File Tool Operated						
Product					i				1	
Capacity	6 x 3	13 x 3	4 - 6	8 - 10	13 x 3	13 x 6	AR-	AR-	AR-	AR-
Order Code	GT-613 GT-468		GT-	133	661		666	662		



Polishing Block Stone Code: BG...

For wide surface levelling and chamfering / deburring. EKR: General Steel • SCG: Hard Steel

Order Example	Α	Н	L
BG100. EKR or SCG	16	25	100
BG125. EKR or SCG	20	40	125
BG150. EKR or SCG	25	50	150
BG200. EKR or SCG	25	50	200



Mini Cutting Disc

It is used in cutting operation of all metals including

hard steels at Rotary Tools.

Order Code	d	k	Mandrel
KS25	25	0.65	Ø 0 0F
KS40	40	1.0	Ø 2.35 mm Ø 3.0 mm
KS60	60	1.5	9 0.0 mm



Fiber Ceramic Polishing Stones

"SG" Fiber Ceramic Polishing Stones are the excellent stones for detail polishing. They prepare d by pressing with resin binder spraying screened, gauged micron diamond particles on powerful fiber textured ceramic, "SG" Ceramic Stones have the feature of resistance with flexible structure againts breakage.

Optimal for premium polishing of flat surfaces, hard to reach slots, ribs and corners. High polishing productivity can be obtain without clogging. "SG" Ceramic Stones can be used in our Air File Tools or by hand (please see below for manual holders).

Fiber Ceramic Polishing Stones Types

ribor coramic renorming eterice Types						
G	Grit Code					
SGCS	C	# 180				
SGCS	0	# 250				
SGCS	D	# 280	Thickness: 1 mm	Diameter: 3 mm		
SGCS	N	# 360	Width x Length	Diameter		
SGCS	В	# 400	1 x 4 x 100			
SGCS	Y	# 700	1 x 6 x 100	Ø 3 x 100		
SGCS	R	# 1200	1 x 10 x 100			

Order: Grit Code. Dimension Order Example: SGCSO. 1 x 6 x 100

Fiber Ceramic Polishing Stone, Manual Holders



"Strong Fiber Texture & Durable Structure"











"SG" Ceramic Stones suitable to be used in Air File Tools. Refer to "page-371" for Air File Tools.



