## Güvenal 🕮



## **Tool Post Grinders** On Lathe / for Internal & External Grinding


## Code: ST..

It is an excellent machine for internal / hole grinding with easy to mount to the lathe. During the internal works, it maintains many diffucult operation, in addition to external grinding operation together.

- 15 / 20% material removal.
- Internal grinding up to 150 mm (up to 600 mm with additional apparatus).
- Surface / flat grinding operation with Cup Grinding Wheel.

The installation is made by placing a flange on the part of the lathe where the tool holder is located. As all lathes have different axis, the lathe axis is referenced. You can request assistance from our company for installation and training.





Specification	Order Code: ST175
Motor Power	0.5 HP / 380 V ~ 50 Hz
Rpm	2800
Grinding Wheel	175 x 20 x 20 (25 / 32)
Suitable Lathe	1000 and 1500 mm

Specification	Order Code: ST201
Motor Power	1 HP / 380 V ~ 50 Hz
Rpm	2800
Grinding Wheel	200 x 20 x 20 (25 / 32)
Suitable Lathe	2000 mm

Specification	Order Code: ST202
Motor Power	2 HP / 380 V ~ 50 Hz
Rpm	3000
Grinding Wheel	200 x 20 x 20 (25 / 32)
Suitable Lathe	2000 mm and over





## Work Safety Products for Mould Polishing Operation

Order Code	Product
КВК	Ear Protection
KLK	Earplug
STM	Dust Mask
VTM	Dust Mask with Valve
KG01	Safety Goggles