



Grafitli, Bronz Kam Plaka - VDI 3357

Kod: G 109

b	l	t	l1	a	w
100	170	45	143.37	60	20°
125				85	
150				110	
100	150	60	127.86	60	30°
	170			85	
125	150	45	127.86	85	
	170	60		110	
150	150	45	127.86	110	
	170	60			

Kendinden Yağlamalı Açılı Sürtünme Plakaları, Kam Ünitesi Üst ve Alt Gövdesi İçin
Delik mesafeleri arasındaki tolerans: ± 0.25 .
Tolerans belirtilmeyen tüm ölçülerde ± 0.25 kullanılır.

Malzeme: Bronz + Grafit



Sipariş: G 109. b x l x t

Çelik Kam Plaka - VDI 3357

Kod: G 109C

b	l	t	l1	a	w
100	170	45	143.37	60	20°
125				85	
150				110	
200	160				
100	150	60	127.86	60	30°
	170			85	
125	150	45	127.86	85	
	170	60		110	
150	150	45	127.86	110	
	170	60		160	
200	150	45	127.86	160	
	170	60			

Çelik Açılı Sürtünme Plakaları, Kam Ünitesi Üst ve Alt Gövdesi İçin
Delik mesafeleri arasındaki tolerans: ± 0.25 .
Tolerans belirtilmeyen tüm ölçülerde ± 0.25 kullanılır.

Malzeme: 1.2379
Sertlik: 63 - 65 HRC



Sipariş:
G 109C. b x l x t