



**Flexible Cooling Hose** Code: **PSE**

Even at high pressures, it guarantees the directional stability. Resistant to all chemicals. Combine system with modular passing feature.

**1/4" Operating Pressure:**

6 Bar / Flow Rate 15 l. / min.

**3/8" Operating Pressure:**

6 Bar / Flow Rate 25 l. / min.

Order Code	Thread	Length
PSE.14	1/4"	280 mm
PSE.38	3/8"	320 mm

It can be supported with "Ball Valve" as per request.



**Rubber Hose (gas & air)** Code: **HSG**

\* Double layer hoses with rope.

\* When ordering, specify desired meter.



Order	Inner	Outer
HSG.08	5	8.5
HSG.10	8	10.5
HSG.13	10	13.5
HSG.16	9.5	15.4
HSG.19	12.5	18.5

**Mini Ball Valve** Code: **KKV**



\* Manual controlled.

\* Button type ball valves.

\* 1/4 male threaded regulator.

Order Code	Female	Male
KKV.13	G 1/4"	G 1/4"
KKV.17	G 3/8"	G 3/8"
KKV.21	G 1/2"	G 1/2"
KKV.26	G 3/4"	G 3/4"
KKV.33	G 1"	G 1"

**Hose Clamp (stainless)** Code: **HKI**

Order Code	Capacity
HKI.1016	10 x 16
HKI.1220	12 x 20
HKI.1319	13 x 19
HKI.1623	16 x 23
HKI.2032	20 x 32



**O-Ring Set**



- \* 368 pcs.
- \* 30 different sizes.
- \* NBR Rubber resistant to oils and acids.
- \* 60-90 shore hardness.

**Content:**

From Ø 3 to Ø 30 mm.

**Thickness:**

2 - 2.5 - 3 - 4 mm.

Order Code: ORING.SET

**Teflon Sealing Tape**

Order Code: **TEFLON**

12 metre x 12 mm



**Liquid Gasket Sealant**

\* 300° heat resistance sealing.

Order Code: **SK404** Red

Order Code: **SM404** Blue



Package: 45 g.

**Repair Paste** Order Code: **SUNFIX**

It is especially for water leakage.

Easy to use and versatile problem solver paste for repair, maintenance and construction.

Cold-curing two-component paste suitable for sealing, bonding, moulding, repairing and filling.



**Liquid Sealant with Teflon (PTFE)** Order Code: **W610511**



It is recommended when teflon tape or other thread sealants have been applied. It provides high quality sealing.

**Usage Area:**

- Mould cooling parts (fittings etc.)
- Fastener and pipes
- In all cases requiring sealing

- Handling strength: 20 - 40 min.

- Functional strength: 1 - 3 hours

- Heat resistance: -55 / +150° C

- Gap filling capacity: 0,30 mm

Package: 50 ml.

**Cooling Adapter** Code: **DSN**



Order	Thread	Length	Hexagon
DSN.02	1/8"	22	14
DSN.03	1/4"	26	17
DSN.04	3/8"	26	22
DSN.05	1/2"	30	27

**Cooling Adapter** Code: **ONE**



Order	Thread	Length
ONE.01	1/8"-1/8"	21
ONE.02	1/8"-1/4"	23
ONE.03	1/4"-1/4"	23
ONE.04	1/4"-3/8"	23
ONE.05	1/4"-1/2"	29
ONE.06	3/8"-3/8"	23
ONE.07	3/8"-1/2"	29

**Reduction Fitting** Code: **DEN**



Order	Female	Male
DEN.01	G 1/8"	G 1/4"
DEN.02	G 3/8"	G 1/4"
DEN.03	G 1/8"	G 3/8"
DEN.04	G 1/8"	G 1/2"
DEN.05	G 1/4"	G 3/8"
DEN.06	G 1/4"	G 1/2"
DEN.07	G 3/8"	G 1/2"

**Cooling Fitting - Elbow** Code: **KDR**



Order	Male
KDR.10	G 1/8"
KDR.13	G 1/4"
KDR.17	G 3/8"
KDR.21	G 1/2"
KDR.26	G 3/4"
KDR.33	G 1"

**Hose Fitting** Code: **HBE & HBF**



HBE	HBF	Order	Order	Male
		HBE.6	HBF.6	6.0 mm
		HBE.9	HBF.9	9.5 mm
		HBE.13	HBF.13	12.5 mm
		HBE.16	HBF.16	13.5 mm
		HBE.19	HBF.19	18.5 mm